



Electronic Euro-Depth Gages



Fowler's new Euro-Depth Gages feature Direct RS232 Output. These low cost tools combine Fowler's Swiss patented measuring system with the rugged design of a full 8" and 12" capacity depth gage. Together they replace conventional vernier and dial depth gages and depth micrometers.

Special Features:

- Features a standard style end.
- Base width: .300"
- Beam width: .637"
- Beam thickness: .120"
- Large easy to read LCD display
- Resolution: .0005" (.01mm)
- Direct inch/metric conversion
- Incremental floating zero
- Low drain, high efficiency lithium wafer battery (environmentally safe for disposal) offers 3000 hours of continuous on-time. Life extended 2—3 years with use of on/off switch.
- Includes battery & deluxe wood case.



No. 54-137-008



No. 54-137-012



Range	Max Error	Squareness
8"	.0015"(.04mm)	.0006"(.015mm)
12"	.002"(.05mm)	.0012"(.03mm)

Order No.	Description
54-137-008	8"/200mm Euro-Depth Gages, base length = 4"/100mm.
54-137-012	12"/300mm Euro-Depth Gages, base length = 6"/150mm.
54-100-350	Replacement lithium battery (type CR2032 or BR2032).
54-115-333	Simplex Computer Kit. Includes 80" (2m) connecting cable 9 pin IBM ATRS-232 connector; software support disk & instructional manual.