

Fred V. Fowler Company, Inc.



Heavy Duty Electronic Scales



No. 54-998-112



Heavy-duty, lightweight with readout, Sylvac's Digital Scales are equipped with a fixing clamp on both ends. It can be mounted by four M5 screws—center distance of holes .71"(18mm). Two tapped M3 holes on each side of the housing allow mounting to appropriate equipment.

Special Features:

- Section of scale: 1.26 x .31" (32 x 8mm).
- Dimensions of housing: 4.72 x 2.76 x .83" (120 x 70 x 21mm).
- The main beam is hardened stainless steel box construction filled with epoxy resin for stability, strength and lightness.
- Hold feature freezes display for later viewing. Ideal for hard to reach places.
- Incremental floating zero. Deviations are read out directly with no math.
- Large, high-contrast LCD display indicates in/mm, hold and zero functions.
- Low drain, high efficiency lithium wafer battery offers 4500 hrs. continuous on time.
- Direct inch/metric conversion.
- Direct RS232C output connects tool to any computer or printer without an interface.

Order No.	Range	Overall Length	Accuracy
54-998-108	8"/200mm	16"/400mm	.0015"
54-998-120	20"/500mm	28"/700mm	.002"
54-998-124	24"/600mm	32"/800mm	.002"
54-998-130	32"/800mm	40"/1000mm	.0025"
54-998-140	40"/1000mm	48"/1200mm	.0028"
54-115-333	Simplex Connecting Kit. Includes 80"(2m) connecting cable with 9 pin IBM compatible connector, support disk and instruction book.		
54-100-350	Replacement lithium battery (type #CR2030 or BR2032)		

* Scales up to 4000mm are available upon special request.